



Bedrock
■■■■■■■■■■

Bitumen Emulsion SS-1astm

● Slow Setting Emulsion astm as per ASTM D 2397

✉ sales@bedrockinfra.com

☎ +91 7888230863

🌐 www.bedrockinfra.com



Bitumen Emulsion SS-1 astm

Slow-Setting-1 bitumen emulsion is specially designed water based bitumen emulsion with low viscosity and extended setting time. SS-1 emulsion is mainly used for Prime Coat. Slow Setting-1 emulsion is manufactured strictly as per ASTM D2397.

CERTIFIED BY:



Specifications

Properties	Slow Setting-1 astm
Residue on 600 micron IS Sieve, % Max	0.01
Viscosity @ 50 ° C(Saybolt Viscometer), Sec	20-100
Storage Stability after 24 Hours, %	Less than 2
Coagulation at low temperature	Nil
Cement mixing test	2.0 %(Max)
Miscibility with water	No Coagulation
Residue by evaporation, percent, Min	57%(Min)



Advantages

- > Better Shelf Life
- > Better particle size distribution
- > Extended setting time
- > Good adhesion properties
- > Easy to spray



Applications

Slow Setting-1 (SS-1) used for fog seal, crack seal & prime coat.



Packing

Bedrock is supplying bitumen emulsion in bulk and in HDPE/MS drum



Bedrock Chem Infra LLP



421/3, Palsai, Wada, Palghar, Maharashtra, 421312



sales@bedrockinfra.com



+91 7888230863



www.bedrockinfra.com